

Rimage 2000i Specifications

This document provides product specification information for the Rimage 2000i autoloader. For more information on how to operate and identify the parts of the Rimage 2000i, refer to the *Rimage 2000i User Guide*.

 **Notes:**

- The most up-to-date 2000i specification information is found in the current revision of this document.
- 480i printer specifications as well as other manuals referred to in this document are available at www.rimage.com/support. From the Support menu select: **Product Series > Product Name > User Manuals** tab.

		Rimage 2000i
Standard system		The standard system includes the Rimage 2000i autoloader (with the integrated Rimage 480i printer assembly) and Rimage 2000i Software.
Number of recorders		2
Bin capacity		
	Supply bin	100 discs
	Output bin	100 discs
Physical size		
	Height	21.0 in (53.3 cm)
	Width	15.75 in (40.0 cm)
	Depth*	20.0 in (50.8 cm)
	Weight	62.0 lb (28.12 kg)
		*Leave an additional 3.5 in (9 cm) for cabling.
Software requirements		The Rimage 2000i ships with Rimage 2000i Software™. The Rimage 2000i operates with either Rimage 2000i Software or Rimage OfficeNET™ Software Suite. To purchase OfficeNET Software Suite, contact your Rimage reseller.
Media requirements		Use only 120 mm optical discs that are coated with an ink-jet printable surface. The media in Rimage Media Kits™ are designed for optimum print performance. Learn more about Rimage Media Kits™ at www.rimage.com .

Rimage 2000i	
Minimum PC requirements	<p>ⓘ Important! If you do not understand these requirements, ask your computer technician for help or refer to your PC documentation.</p> <ul style="list-style-type: none"> • Windows Vista Business SP2 • Windows Vista Enterprise SP2 • Windows Vista Ultimate SP2 • Windows XP Professional SP3 • Windows Server 2003 Standard SP2 <p>Supported operating systems (32-bit only)</p> <p>Processor Pentium 4, 2.8 GHz or faster</p> <p>RAM/Memory 1GB</p> <p>Ports Use an integrated high-speed USB 2.0 port (using a USB expansion card is not recommended)</p> <p>Fixed storage Two 7,200 RPM hard drives with 10 GB free space on each drive ***</p> <p>Removable storage CD/DVD-ROM</p> <p>Graphics 1024 x 768 screen resolution, 16-bit color</p>
Networking ability	Refer to the <i>Rimage Advanced Setup (Networking) Guide</i> for instructions on submitting orders from a networked computer.
Print quality	<p>Technology Thermal inkjet printing</p> <p>Resolution Up to 4800 dpi</p> <p>Droplet size 3 pico-liters</p> <p>Pixel density 5.76 million pixels per square inch</p>
Power	100 – 240 VAC, 2.7 A, 60/50 Hz
Temperature and humidity	<p>Operating temperature 60° to 95° F (16° to 35° C)</p> <p>Humidity 40% to 80% non-condensing</p> <p>Storage temperature 5° to 95° F (-15° to 35° C)</p>