

# Rimage Professional™ 5100N and 5300N Specifications

This document provides product specification information for the Rimage Professional 5100N and 5300N autoloaders. For more information on how to operate and identify the parts of the 5100N or 5300N, refer to the *Rimage Professional™ 5100N and 5300N User Guide*.

• **Notes:**

- The most up-to-date technical specification information for the Professional 5100N and 5300N is found in the current revision of this document.
- For printer specifications, refer to the Everest printer specifications document available on the [www.rimage.com/support](http://www.rimage.com/support). From the **Support** menu select: **Printer Series > Product Name > User Manuals** tab.

|                                | 5100N   | 5300N   |                     |
|--------------------------------|---|---|---------------------|
| <b>Standard system</b>         | Rimage Professional 5100N, Everest printer, and Rimage installed software   | Rimage Professional 5300N, Everest printer, and Rimage installed software |                     |
| <b>Number of recorders</b>     | 1   | 2   |                     |
| <b>Input bin capacity</b>      | 1 input bin, 50 discs per bin   | 2 input bins, 50 discs per bin  |                     |
| <b>Output bin capacity</b>     | One 75-disc output bin  | Five single-disc output trays and one 100-disc output bin                 |                     |
| <b>Physical size</b>           | <b>Height</b>   | 19.25 in (48.90 cm)   | 29.25 in (74.30 cm) |
|                                | <b>Width</b>  | 15.00 in (38.10 cm)   | 15.00 in (38.10 cm) |
|                                | <b>Depth*</b>   | 23.38 in (59.39 cm)   | 23.38 in (59.39 cm) |
|                                | <b>Weight</b>   | 53 lb (24.04 kg)  | 67 lb (30.39 kg)    |
|                                | <b>Weight with Everest</b>  | 98 lb (44.45 kg)  | 112 lb (50.80 kg)   |
|                                | * Leave an additional 3.5 in (9 cm) for cabling.  |   |                     |
| <b>Minimum PC requirements</b> | <b>Supported operating system:</b><br>The supported operating system is installed on the embedded PC. Only the installed operating system is supported on this product. |   |                     |
| <b>Software requirements</b>   | The required software is installed on the embedded PC.  |   |                     |

|                                  | 5100N   | 5300N |                              |                                 |                 |                           |                            |                             |
|----------------------------------|---|-------|------------------------------|---------------------------------|-----------------|---------------------------|----------------------------|-----------------------------|
| <b>Networking ability</b>        | To submit orders from a networked PC, refer to the <i>Rimage Advanced Setup (Networking) Guide</i> .  |       |                              |                                 |                 |                           |                            |                             |
| <b>Power</b>                     | 100 – 240 VAC, 60/50 Hz, 4.7 – 3.7 Amp, 500 watt maximum  |       |                              |                                 |                 |                           |                            |                             |
| <b>Media requirements</b>        | Refer to your <i>Everest User Guide</i> for the correct media requirements. Rimage Media Kits™ are designed for optimum recording and print performance.  |       |                              |                                 |                 |                           |                            |                             |
| <b>Ribbon requirements</b>       | Refer to your <i>Everest User Guide</i> for the correct printer ribbons. Rimage Media Kits include the required print ribbons.  |       |                              |                                 |                 |                           |                            |                             |
| <b>Label design requirements</b> | Refer to your <i>Everest User Guide</i> for label design requirements.  |       |                              |                                 |                 |                           |                            |                             |
| <b>Temperature and Humidity</b>  | <table border="0"> <tr> <td style="padding-right: 20px;"><b>Operating Temperature</b></td> <td>60° to 80° F (15.5° to 26.7° C)</td> </tr> <tr> <td><b>Humidity</b></td> <td>40% to 80% non-condensing</td> </tr> <tr> <td><b>Storage temperature</b></td> <td>5° to 95° F (-15° to 35° C)</td> </tr> </table> |       | <b>Operating Temperature</b> | 60° to 80° F (15.5° to 26.7° C) | <b>Humidity</b> | 40% to 80% non-condensing | <b>Storage temperature</b> | 5° to 95° F (-15° to 35° C) |
| <b>Operating Temperature</b>     | 60° to 80° F (15.5° to 26.7° C)   |       |                              |                                 |                 |                           |                            |                             |
| <b>Humidity</b>                  | 40% to 80% non-condensing   |       |                              |                                 |                 |                           |                            |                             |
| <b>Storage temperature</b>       | 5° to 95° F (-15° to 35° C)   |       |                              |                                 |                 |                           |                            |                             |